

LD Zijkanaalventilatoren – Capaciteit / Overdruk

ZIJKANAALVENTILATOREN VOOR OVERDRUK TOEPASSINGEN—50 Hz													
DRUKVERSCHIL	mbar												
			50	75	90	125	150	170	200	220	250	280	340
TYPE	kW	Maximum drukverschil mbar	FLOW BIJ BOVENGENOEMD DRUKVERSCHIL										
			m3/h										
ZDI40-018-1H 1-fase	0,18	65	27										
ZDI40-018-3H	0,18	65	27										
ZDI80-1-040-1H 1-fase	0,40	130	60	48	40	20							
ZDI80-1-040-3H	0,40	130	60	48	40	20							
ZDI150-1-075-1H 1-fase	0,75	160	110	90	82	70	60						
ZDI150-1-075-3H	0,75	140	110	90	82	70	60						
ZDI150-1-090-3H	0,9	180	110	90	82	70	60	50					
ZDI150-1-11-1H 1-fase	1,1	190	110	90	82	70	60	50					
ZDI150-1-11-3H	1,1	200	110	90	82	70	60	50	38				
ZDI210-1-15-1H 1-fase	1,5	200	170	150	145	125	110	100	84				
ZDI210-1-15-3H	1,5	220	170	150	145	125	110	100	84	72			
ZDI210-1-22-3H	2,2	270	170	150	145	125	110	100	84	72	58		
ZDI320-1-22-3H	2,2	220	260	245	230	210	190	175	150	145			
ZDI320-1-3-3H	3	280	260	245	230	210	190	175	150	145	125	110	
ZDI320-1-4-3H	4	340	260	245	230	210	190	175	150	145	125	110	72
ZDI550-1-4-3H	4	230	450	420	405	390	365	350	325	315			
ZDI550-1-55-3H	5,5	300	450	420	405	390	365	350	325	315	300	285	
ZDI550-1-75-3H	7,5	400	450	420	405	390	365	350	325	315	300	285	245
ZDI1100-1-13-3G	13	290	1050	1020	1000	955	930	890	850	810	700	620	